



Blue Magic XLf 200 A

Sales start
July 2012

Order number
1 061 110 581 001

EAN number
001 396 408 153 4

Highlights

- Active Subwoofer enclosure with integrated Class-D Amplifier
- Small dimensions: 340 x 71/79 x 225 mm, therefor easiest mounting, e.g. even under the front seats
- Digital Amplifier with high power output:
150 Watts RMS / 300 Watts Max. Power
- 200mm/8" Subwoofer with Aluminum Compound Cone
- Perfectly matching subwoofer with high rated and peak power handling
- Easiest connection - only 12 volts/ground signal + the signal from the speakers or pre-amplifier required
- Automatic power-on via high level or RCA/Cinch input – no remote signal required
- Housing material: aluminum die-cast/fiberglass reinforced ABS
- EPC compatible: easy connection via optional cable for power, ground and speaker signal (Easy Power Connection EPC)





Blue Magic XLf 200 A

1 061 110 581 001

Technical Data:

Amplifier

- Type: Class-D
- RMS Power (watts): 150
- Max. Power (watts): 300
- Frequency response(Hz): 20-150
- Low-pass filter crossover frequency(Hz): 50-150
- Phasing control(°): 0 - 180
- Input sensitivity(V): 0.1 - 9
- Signal/noise ratio dB/A (dB): >92 dB
- Audio-In : 2x Cinch/RCA, 2x Highlevel
- Automatic power-on - no remote signal required!
- After 60 sec. without any signal the amplifier will automatically switch off
- Operation indicator: dual-color LED (green / red)

Subwoofer

- Diameter (mm): 200
- Cone material: Aluminum Compound
- Cone color: blue metallic
- RMS power handling (watts): 150
- Peak power handling (watts): 300
- Impedance (ohms): 0.6
- Frequency response (Hz): 20 - 150
- Sound pressure level 2.0 V/m (dB): >92

Enclosure

- System: closed box
- Material: aluminum die-cast / fiberglass reinforced ABS
- Housing color: dark silver
- Height x Width x Depth (mm): 340 x 225 x 79
- Height x Width x Depth (inch): 13.4 x 8.7 x 3.1

Scope of delivery

- Subwoofer enclosure
- Adapter cable for highlevel connection
- Fuse 10A
- User manual
- Installation material: metal strip, special screws

