

### FEATURES

- High resolution CMOS camera (1.23 Mega pixels)
- 1/3.2" Color CMOS high resolution image sensor
- Waterproof Housing (IP69K rating)
- Automatic Electronic Iris
- Mirror Image (Normal image function via loop wire)
- Diagonal 160° Viewing angle
- Compact Aluminum Housing
- Easy installation (flushmount)
- Temperature Range -40°C to +80°C
- Vibration resistant (5G)
- Extra thick glass window (3mm)
- Suitable for  $\Phi$  25mm drilling hole
- Waterproof screw type connector, 4-pin mini-DIN
- Various angled washers included
- ECE R10.05 approved (EMC)



### Specifications

<b>Image Sensor</b>	1/3.2" Color Sony CMOS (Exmor)
<b>Effective Pixels</b>	CVBS - PAL, 1.23 Mega pixels, 1280(H) x 960(V)
<b>Minimum Illumination</b>	1 lux
<b>Video Output</b>	75 $\Omega$ , 1.0Vp-p
<b>Power Range</b>	DC 9V ~ 32V
<b>Power Consumption</b>	DC 12V, 70mA
<b>Operation Temperature</b>	-40°C to +80°C
<b>Lens Viewing Angle</b>	115° Horizontal, 86° Vertical, 160° Diagonal
<b>Material</b>	Compact Aluminum Housing
<b>Dimensions</b>	Head part : $\Phi$ 40.2 mm Main body : $\Phi$ 25.0 mm Total length : 56.44 mm Flushmount depth: approx. 46.50 mm
<b>Weight</b>	Approx. 145g
<b>Accessories</b>	1 set 15° washers, 1 set 6° washers, 1 set straight spacers