

Top Tec ATF 1400

DESCRIPTION

Top Tec ATF 1400 is a high performance automatic transmission fluid of the new generation based on synthetic technology. It was developed specifically for use in CVTs with thrust link belt or a gear chain made of steel. The basis of modern base oils and select additives offer the best possible anti-froth protection, which is necessary for CVTs. It also features a very good stability against aging and oxidation. Top Tec ATF 1400 is tried and tested, most notably in the Mercedes-Benz A-Class and B-Class Autotronic transmissions and in continuously variable automatic transmissions (Multitronic) in Audi vehicles.

PROPERTIES


- Excellent viscosity/temperature properties
- Best possible anti-froth protection
- Excellent low-temperature properties
- Very good aging and oxidation stability
- Outstanding protection against wear and good friction characteristics
- Optimum corrosion protection

Specifications and approvals:

LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:

Audi/ VW G 052 180
MB 236.20
Ford CVT30 / MERCON® C
Ford CVT23
Toyota TC
Hyundai SP-III
Kia SP III
Mitsubishi SPIII
Mitsubishi CVTF-J1
Nissan NS-2
Honda HMMF
Subaru NS-2 / Lineartronic CVTF
Mini Cooper (EZL 7/99)
Suzuki TC / NS-2 / CVT Green 1
GM / Saturn DEX-CVT
Dodge NS-2 / CVTF+4
Jeep NS-2 / CVTF+4

Note: Not suitable for hybrid CVT (Honda, Ford)!



.../2

PRODUKTINFORMATION



TECHNICAL DATA

Density at +15 °C	: 0.851	g/cm ³	DIN 51757
Brookfield viscosity -40 °C	: < 12,000	mPas	DIN 51389
Viscosity at +40 °C	: 33.0	mm ² /s	DIN 51562
Viscosity at +100 °C	: 7.0	mm ² /s	DIN 51562
Viscosity index	: 189		DIN ISO 2909
Flash point	: 204	°C	DIN ISO 2592
Pour point	: -48	°C	DIN ISO 3016
ASTM color	: L2,5		DIN ISO 2049

AREAS OF APPLICATION

For the new generation of CVTs with thrust link belt or a gear chain made of steel.

APPLICATION

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

AVAILABLE PACK SIZES

Top Tec ATF 1400	1 l	Part no. 3662 D-GB-I-E-P
	1 l	Part no. 8041 D-RUS-UA
	20 l	Part no. 3692 D
	205 l	Part no. 3661 D

PI 06/06/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

